



IMPORTANT

Disconnect power before installing fixtures. Read instructions before starting work. This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Saturna 4020T Series

FIXTURE INSTALLATION INSTRUCTIONS

- 1 Remove luminaire from shipping cartons. Remove mounting plate from arm assembly.
- 2 Position mounting plate over junction box pull supply leads through hole in mounting plate. Check for square and fasten to ears of junction box (temporary mounting only) permanently mount plate to wall through (4) mounting holes with appropriate hardware. (Not provided).
- 3 Connect black, white and green leads (supplied) to supply leads with approved wire connectors (not provided). Push connections securely into junction box.
- 4 Remove (3) screws and wiring access plate from arm assembly and put to one side.
- 5 Hook arm assembly over mounting plate, feed wires through arm and out bottom of access plate opening. Tighten (2) set screws at bottom of arm assembly until arm is secure against wall.
- 6 Silicone seal the top and two sides of arm assembly against wall to prevent water ingress caused by uneven surface textures.
- 7 Place housing assembly over arm assembly feeding wires through bottom of access plate opening. Tighten (3) set screws.
- 8 Connect black, white and green leads. Push wires into arm assembly and re-install access plate.
- 9 Energize and test as required.