



IMPORTANT

Disconnect power before installing fixtures. Read instructions before starting work. This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Orchestra Circle 2756W LED Series

ARM INSTALLATION INSTRUCTIONS

- 1 Remove luminaire components from cartons.
- 2 Attach LED driver tray to end cap assembly through key holes and tighten hex nuts provided.
- 3 Remove end cap screws (2) from end cap assembly.
- 4 Slide arm assembly on to driver tray / end cap assembly / head assembly. Feed the supply wire leads through the arm assembly. Re-attach end cap screws (2) removed in previous step. Be careful not to pinch wires from head assembly.
- 5 Connect the black, white and green wire leads from LED driver to the supply leads from the J-Box and push these connections carefully into the J-Box.
- 6 Position mounting plate over a standard 4" octagon Junction Box (by others) ensure mounting plate is centered in desired position. Orchestra head facing down as per specification page and diagram.
- 7 Secure to wall surface through holes provided in wall plate. Mounting hardware is not provided. Mounting hardware should be suitable for type of wall material and load application.
- 8 Reflector disks (2) are attached with hardware provided at the top location as per diagram.
- 9 Energize and test as required.
- 10 This fixture is supplied with an LED as specified for the project and is self contained.
- 11 For exterior / wet locations, silicone sealant should be applied between the wall surface and the arm mounting plate to exclude water entrance.

REV. 09/18/17