



IMPORTANT

Disconnect power before installing fixtures. Read instructions before starting work. This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN

Saturna 4005/4004 LED Series

FIXTURE INSTALLATION INSTRUCTIONS

1. Remove luminaire components from shipping cartons.
2. Loosen (2) set screws from bottom of wall arm assembly and remove mounting plate.
3. Position mounting plate on wall surface. Ensure that it is level and secure against the wall surface. Mounting plate should be attached to wall surface independently from the junction box with suitable hardware for the type of wall (hardware by others).
4. Connect the black, white and green wire leads from the LED driver to the supply leads from the J-Box and push these connections carefully into the J-Box.
5. The wall arm assembly hooks over mounting plate and is secured with (2) set screws loosened in step 2. Do not over tighten but ensure assembly is secured against wall surface.
6. The glass lens/jar screw threads on to the LED head. Ensure glass lens is not cross threaded and should be tightened up to the fitter gasket.
7. Remove (3) acorn nuts from cage assembly.
8. Attach cage assembly to LED head and re-attach (3) acorn nuts removed in step 7.
9. Energize and test as required.
10. This fixture is supplied with an LED as specified for the project and is self-contained.
11. For exterior / wet locations, silicone sealant should be applied to the top and down both sides of the wall arm canopy to exclude water entrance. Sealant between wall surface and wall arm shepherd's hook LED head assembly.

REV. 2/13/18