

Saturna 5009CLED Recessed Wall Cut Off Face

EXTERIOR


MODEL	LAMP	COLOR TEMPERATURE	VOLT	OPTIONS	COLOUR
5009C	9L	9 watt LED module ¹ 40* 4000K	120*	OPC polycarbonate diffuser	WT white texture
	13L	13 watt LED module ¹ 30 3000K	277	DIM 0-10 volt dimming driver	BT black texture
			347 ²		SM silver metallic
					AN aluminum natural
					BZ bronze
					GM gunmetal
					WS white satin
					BM black matte
					RAL specify no.

*Standard configuration unless otherwise specified ¹LED Power ²Only available in 13L version

SAMPLE CATALOG NUMBER: 5009C - 13L - 40 - 120 - WT

Using this catalog number would order 1 model 5009CLED recessed wall cutoff face luminaire with cutoff guard and a 13 watt LED module at 4000K wired to 120 volts, painted with white texture polyester powder coat.

CONSTRUCTION	MOUNTING	OPTICAL	PROTECTION
<p>Materials Concrete pour housing: Polyester powder coated .064" aluminum. Splay trim: Aluminum. Frame: Die cast, heavy wall, marine grade aluminum. Lens gasket: Extruded EPDM, fully gasketed around glassware. Exposed fasteners: Stainless steel allen drive cap screws, captivated.</p> <p>Electrical Components Driver: Constant current 350mA or 250 mA. LEDs: COB with Zhaga compliant socket, 80 CRI standard.</p>	<p>The Saturna 5009C is designed for concrete pour wall installations. (See installation instructions on www.rebellelighting.com for further details). Consult factory for concrete block, masonry or hollow wall constructions. Thru wiring approved for 12ga wire - 4 in / 4 out plus ground. Complies with ADA requirement for less than 4 inch protrusion.</p>	<p>Luminaire provides a cut-off lighting distribution. The LED compartment is contained in the upper hemisphere of the hood guard. A gasketed, prismatic tempered glass lens seals the LED compartment from contamination.</p>	<p>The Saturna recessed wall is CSA/UL listed for wet locations less than four feet from the ground - ADA Compliant. Units are fully gasketed and utilize aluminum castings and glass diffusers for increased weatherability and resistance to corrosion and UV radiation. Life = 50,000 hours. Minimum L70 @ 25°C ambient.</p>



Saturna Recessed 5009CLED Detailed Product Description

- | | |
|---|---|
| <p>1 Lens Gasket - Extruded E.P.D.M.</p> <p>2 Concrete Pour Box Assembly Polyester Powder Coat .064" Aluminum</p> <p>3 Electrical Tray with LED COB Module</p> <p>4 Glass Diffuser - Tempered Prismatic Gasketed</p> <p>5 Driver - Constant Current</p> | <p>6 Cast Concave Face (Marine Grade)</p> <p>7 Splay Trim - .081" Aluminum</p> <p>External "Thru-Wire" J-Box: (4IN / 4OUT) Die Cast Aluminum (3) 1/2" NPT Openings</p> <p>9 Cast Aluminum Cut Off Face Guard (Marine Grade)</p> |
|---|---|